



E-CHAIN MACHINERY CO., LTD.

No. 276-2, Kuan Chi Road, Shen Kang District, Taichung 42948, Taiwan.

Tel: +886-4-2562-0988

E-Mail: sales@echainmachinery.com

Fax: +886-4-2561-9826

Website: www.echainmachinery.com

Double End Tenoner: ECT-88S(A) (CE-Certified)



Double End Tenoner (CE-Certified)	
SPECIFICATION	ECT-88S(A)
Max. working width	2600mm
Min. working width	320mm
Max. working thickness	80mm
Feed Chaintrack	
Motor horse power	2hp
Feed speed	5-25m/min
Distance between dogs	400mm
Movable Side Shifting System	
Motor horse power	1hp
Feed speed	2m/min
Scoring Saw System	
Motor horse power	2hp
Spindle speed	3000rpm(50Hz)
Spindle diameter	25.4mm
Sawblade diameter	205mm



E-CHAIN MACHINERY CO., LTD.

No. 276-2, Kuan Chi Road, Shen Kang District, Taichung 42948, Taiwan.

Tel: +886-4-2562-0988

E-Mail: sales@echainmachinery.com

Fax: +886-4-2561-9826

Website: www.echainmachinery.com

Main Saw System	
Motor horse power	7.5hp
Spindle speed	3000rpm(50Hz)
Spindle diameter	25.4mm
Sawblade diameter	255mm
1st Moulding System (high-frequency motor) (equipped with jumping function)	
Motor horse power	5hp
Spindle speed	3000-8000rpm
Spindle diameter	40mm
Cutter diameter	180-210mm
2nd Moulding System (high-frequency motor) (tiltable to $\pm 90^\circ$)	
Motor horse power	7.5hp
Spindle speed	3000-8000rpm
Spindle diameter	40mm
Cutter diameter	180-210mm
Weight	
N.W.	4480kg
G.W.	5120kg
Dimensions	
Machine size (mm)	4560x3460x1470mm
Packing size (mm)	4760x2280x1750mm